

Touch Dynamic PR-IM



PR-IM

Highlights

- Clamshell design for easy paper loading
- Internal power supply
- 2-color, high quality graphics print
- Spill-proof & heat resistant
- Swappable interfaces available
- Wall mount
- External buzzer option
- Epson compatible



TOUCH DYNAMIC

IMPROVING TOUCH TECHNOLOGY

Touch Dynamic • 17 Camptown Road • Irvington, New Jersey 07111
888.508.6824 • www.touchdynamic.com

Touch Dynamic PR-IM-700 Touch Data Sheet

Features Hardware	<p>Hardware You really can have it all!</p> <ul style="list-style-type: none"> - All in ONE Box (except cables, all is included with the printer) - Ultra fast & reliable - Spill-proof design - Clamshell design - Embedded Power Supply - Small footprint - 2-color printing - ESC/POS emulation supported 	<p>Software (included in Windows™ Drivers) The included Receipt Redesign Software allows you to EASILY:</p> <ul style="list-style-type: none"> - Add images (Logos, Coupons, and more!) - Create a Virtual Serial Port for legacy applications - XP & Vista WHQL Certified - Replace text <p>Also included:</p> <ul style="list-style-type: none"> - Ethernet setup utility - Memory Switch setting utility
Connectivity	<p>25-pin serial Parallel USB Ethernet Wi-Fi</p>	<p>Virtual Serial Port to USB Virtual Serial Port to Ethernet</p>
Drivers	<p>Windows 98, ME NT 4.0 WEPOS 2000, XP CE XP Embedded VISTA (32- and 64 bit)</p>	<p>OPOS Java POS Linux Mac OSX</p>
What's included	<p>5 ft. power cord* Internal Power Supply 58 mm guide Power switch cover</p>	<p>Software solutions Virtual Serial Port Setup guide</p>
Optional Accessories	<p>Kitchen buzzer Wall Mount Brackets</p>	
Technical Specifications	<p>Print Method: 9 Pin Impact Dot Matrix Print Speed: 13 RPM (Receipts Per Minute), (4.7 LPS) Paper Width: (standard) / 70 & 58 mm (with paper guide) Emulation: Star Mode, ESC/POS</p>	<p>Power: 110 to 230 VAC MCBF: 22 million lines Cutter: 1 million cuts Dimensions: W=6.3in, H=6in, D=9.7in</p>