

CD7220/CD3220 CUSTOMER DISPLAY

3. GENERAL SPECIFICATIONS

| ITEM | CD7220D | CD7220 | |
|-------------------------|--|---------------------------------------|---------------|
| Display method | Vacuum fluorescent display | | |
| Display color | Blue green | | |
| Number of characters | 80 characters (20 columns x 2 lines with double side) | 40 characters (20 columns x 2 lines) | |
| Brightness | 700 cd/m ² | | |
| Character type | 96 alphanumeric 13 kinds of international character set and 1 user-define character set | | |
| Character font | 5 x 7 dot matrix, comma, decimal point | | |
| Character size | 9.2mm x 5.25mm | | |
| Character pitch | 8.3mm | | |
| Power supply | 5VDC or 12VDC or 24VDC or 33VDC | | |
| Power consumption | 8W | 4.5W | |
| MTBF(power on time) | 25000 hours | | |
| Dimensions | 230(W)x100(H)x42(D)mm | | |
| Viewing angle | ± 30 degrees | | |
| Rotation angle | Maximum 270 degrees | | |
| Weight | 0.9 Kg | | |
| Environmental Condition | Operating | Temperature | 5 - 45°C |
| | | Humidity | Less then 95% |
| | Storage | Temperature | -5 - 55°C |
| | | Humidity | Less then 95% |
| Safety | FCC class B 、 CE | | |

Table 1-2